

P/N: TA60

Copyright

© 2020, FLIR Systems, Inc.

All rights reserved worldwide. Names and marks appearing herein are either registered trademarks or trademarks of FLIR Systems and/or its subsidiaries. All other trademarks, trade names or company names referenced herein are used for identification only and are the property of their respective owners.

Document identity

Publ. No.: TA60

Commit: 64533

Language: en-US

Modified: 2020-03-17

Formatted: 2020-03-18

Website

<http://www.flir.com>

Customer support

<http://support.flir.com>

Disclaimer

Specifications subject to change without further notice. Camera models and accessories subject to regional market considerations. License procedures may apply. Products described herein may be subject to US Export Regulations. Please refer to exportquestions@flir.com with any questions.



| | |
|----------------------------|--|
| Part number | TA60 |
| Part description | Thermocouple Probe with Adapter |
| | <ul style="list-style-type: none"> Type K thermocouple temperature sensor. Can be used to measure temperature with many meters. Fast responding with a wide general-purpose measurement range. Safety-shrouded banana to banana connection. 2 year warranty |
| Specifications | |
| Temperature range | -40 to 1200°C (-40 to 2192°F) |
| Meter data | |
| Suitable main unit | DM93, CM78 (DM92) |
| Warranty | https://www.flir.com/testwarranty |
| Certifications | |
| Certifications | ITS-90 (JIS C-1602-1995 Class 2) |
| Meter physical data | |
| Weight | 0.06 kg |
| Dimensions (H x W x L) | 15.24 cm x 3.81 cm x 1.27 cm |



Thermocouple Probe with Adapter

P/N: TA60

© 2020, FLIR Systems, Inc.

#TA60; r. 64533; en-US

| Meter physical data | |
|----------------------------------|---|
| Material | ABS plus PC, bronze (nickel plated), PVC |
| Color | Black and yellow |
| Shipping information | |
| Packaging type | Color box |
| Packaging contents | Manual, TA60 |
| Packaging weight: | 0.08 kg |
| Packaging dimensions (H x W x L) | 7.62 cm x 2.54 cm x 16.83 cm |
| Carton weight | 4 kg |
| Carton dimensions | 14.5" x 13" x 8" |
| Carton quantity | 48 |
| EAN-13 | 0793950377604 |
| UPC-12 | 793950377604 |
| Country of origin | Taiwan |
| Tariff code | 9030908822 |
| Technical support | |
| Website | http://support.flir.com |

Compatible with the following products:

- CM44; FLIR CM44: Professional 400A TRMS AC Clamp Meter + Type K
- CM65; FLIR CM65: True RMS 600A Solar Clamp Meter with METERLiNK
- CM78; FLIR CM78: True RMS Clamp/DMM with infrared thermometer and Bluetooth METERLiNK
- CM94; FLIR CM94: True RMS AC/DC 2000A Utility Clamp Meter with LoZ
- DM166; FLIR DM166: Thermal Imaging TRMS Multimeter with IGM
- DM284; FLIR DM284: Imaging Multimeter with IGM
- DM285; FLIR DM285: Industrial Thermal Imaging Multimeter with Datalogging, Wireless Connectivity, and IGM
- DM64; FLIR DM64: HVAC TRMS Digital Multimeter with Temperature
- DM66; FLIR DM66: Electrical and Field Service TRMS Multimeter with VFD Mode
- DM90; FLIR DM90
- DM91; FLIR DM91: Industrial TRMS Multimeter with Datalogging and Wireless Connectivity
- DM92; FLIR DM92: Industrial Digital Multimeter with LoZ and VFD Mode
- DM93; FLIR DM93: True RMS Industrial Multimeter
- TG56; FLIR TG56: Spot IR Thermometer with Thermocouple